PCT

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : **E01B 35/12, E01C 23/01, G01M 5/00**	**A1**	(11) International Publicati n Number: **WO 96/31655** (43) International Publication Date: 10 October 1996 (10.10.96)

(21) International Application Number: PCT/DK96/00159

(22) International Filing Date: 2 April 1996 (02.04.96)

(30) Priority Data:
0372/95   3 April 1995 (03.04.95)   DK

(71) Applicant (for all designated States except US): GREEN-WOOD ENGINEERING APS [DK/DK]; H.J. Holst Vej 5A, DK-2605 Brøndby (DK).

(72) Inventor; and
(75) Inventor/Applicant (for US only): GRØNSKOV, Leif [DK/DK]; Ny Mæglergårds Allé 77, DK-2665 Vallensbæk Strand (DK).

(74) Agent: LARSEN & BIRKEHOLM A/S; Skandinavisk Patentbureau, Banegårdspladsen 1, P.O. Box 362, DK-1570 København V (DK).

(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published
With international search report.
Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.
In English translation (filed in Danish).

(54) Title: METHOD AND APPARATUS FOR NON-CONTACT MEASURING OF THE DEFLECTION OF ROADS OR RAILS

(57) Abstract

Equipement for non-contact measurement of the deflection of a road (2) comprises a self-propelled vehicle with a load (7) which influences at least one wheel (4), the speed of which is measured in the direction of travel. The equipement further comprises a laser device (8) from which at least one electromagnetic beam (9) is directed towards the rodway in the vicinity of the vehicle, and the Doppler frequency change in the reflection (9) is detected. An electronic circuit (10) continuously registers the results of the measurements and herewith the deflection at normal travelling speed.

METHOD AND APPARATUS FOR NON-CONTACT MEASURING OF THE DEFLECTION OF ROADS OR RAILS

Background of the invention

The invention relates to a method for non-contact measurement of the deflection of a road or a rail as disclosed in the preamble to claim 1, and equipment for the execution of this measurement as disclosed in the preamble to claim 6.

The measuring of the movement of train rails and roads under load is of particular interest, in that it is hereby possible to be able to evaluate their carrying capacity, condition, durability and, in certain cases, also direct faults in the surface or the underlying structure, so that repair work can be initiated in the most expedient places.

It is known to measure the deflection of a road, e.g. making use of a so-called Benkelmann's beam which is positioned on the road, after which a vehicle or the like with a heavy load, e.g. 5-15 tons, is driven closely past the measuring beam and the deflection is measured. This is a relatively precise but very slow method for the measurement of the deflection of roads. Vehicles are constructed with such a measuring beam which can intermittently measure the section of a road by movement of the measuring beam, though only at a maximum of 5-10 km/h. When such measurements are to be carried out, it is thus necessary to give serious consideration to the question of security, in that such a slow-moving vehicle is of great danger for the traffic, which means that the measurements must often be shelved for implementation during periods of light traffic, and also while making use of at least one accompanying vehicle with warning signs etc. which, of course, considerably increases the costs of the measurements.

Furthermore, various methods have been developed whereby
the road surface is influenced by a falling weight or the
like, and deflection-like measurements can be made. These
methods are also very slow and provide measuring results

5   only at intervals, i.e. they do not provide continuous
measurements of the road surface.

From the Swedish publication no. 457.807 there is known a
vehicle with a load, e.g. of 5-15 tons, and on which at

10   least two range finders are mounted which measure the
distance to the road surface, e.g. laser-beam measuring
devices, one of which measures the distance to the unloaded
road surface (reference), while the other measures as
closely as possible to the point at which the road surface

15   is influenced by the loaded wheel. If the equipment is
suitably adjusted, such a vehicle is able to be driven
forwards at a reasonable speed. The difference between the
two distance measurements, corrected for angular errors
etc., is subtracted, and the difference constitutes the

20   deflection, i.e. the depression due to the load. Since the
deflection during normal loading on a vehicle wheel, i.e.
of 5-15 tons, is in the order of 1-4 mm, it will be obvious
to those familiar with the art that such difference
measurements will be encumbered with even much greater

25   errors, in that the depression which is to be measured is
in the same order as the irregularities which are normally
to be found in the road surface. Consequently, this method
has not been found to be successful for road measurements.
On the other hand, it could possibly be used for the

30   measurement of the deflection of a railroad track.

Advantages of the invention

By proceeding as disclosed and characterized in claim 1,
35   e.g. while using equipment as disclosed and characterized
in claim 7, the possibility is provided of carrying out

usable measurements at normal driving speed, e.g. at a speed of 70 km/h or faster. With the present invention, it is not distances which are measured, but continuous measurements are made of the speed with which the surface

5   of the road or the rail moves downwards during the passing of the measuring vehicle, and moreover it is possible to carry out continuous measurements of the vertical speed of the road surface or the rail after the passing of the vehicle, i.e. during its resilient movement back to the

10   unloaded state.

When this equipment is mounted on a heavy, self-propelled vehicle, it is possible at suitably high speeds to generate data for the registration and analysis of the carrying

15   capacity and of the condition of the underlying structure. This data is collected electronically by using one or more sensors which measure the speed of the deflection. The sensors are based on laser technique, radar technique or other speed-measuring equipment, and they function by

20   measuring the Doppler frequency change between the radiation emitted and the reflection. At the same time herewith, there is carried out a measurement and registration of the speed of the vehicle in the direction of travel.

25   By measuring at normal driving speed, the risk of disturbing the traffic is avoided and the risk of accident due to the presence of the measuring vehicle is eliminated.

By proceeding as disclosed and characterized in claim 2,

30   e.g. while using one of the devices as disclosed and characterized in claim 8, the possibility is provided with a suitable number of sensors of measuring the whole of the deflection basin which appears around the wheels, and to continuously map this as a basis for carrying out a con-

35   tinuous calculation, e.g. of the rigidity of a road.

Since all of the measurements are carried out continuously
and electronically, extensive data material is obtained
which must naturally be processed in a suitable manner
before it provides any usable results. It is possible here-
5   by to build up a data bank covering known roads or track
sections, and to use these stored results in the construc-
tion of new roads or railway tracks.

In the processing of such large amounts of data, it will be
10   directly possible to read-out various information concern-
ing the maintenance standard of the relevant section. For
example, discontinuations in the data measured will indi-
cate changes in the underlying structure, which e.g. on a
concrete road can be due to a seesawing slab of concrete.

15

By proceeding as disclosed and characterized in claim 3,
e.g. while using one of the devices as disclosed and char-
acterized in claim 9, corrections can be made for possible
measurement errors from emission which is not directed
20   completely at right-angles towards, for example, a road
surface. These angle measurements, e.g. in the form of
inertia references, can be continuously measured and stored
together with the measurements of the Doppler frequency
change signals, and can moreover be used for the servo-
25   control of the equipment, e.g. the laser devices, which
emit the radiations for the measurement of the deflection.

It is also possible to proceed as disclosed and character-
ized in claim 4, e.g. while using a device as disclosed and
30   characterized in claim 10, so that the angle measurements
are carried out in relation to the curvature of the road or
track along which the measuring vehicle is moving, in that
regard is hereby also paid to possible gradients or de-
clines and other deviations in the plane of the roadway or
35   rail element during the course of the measurement.

By proceeding as disclosed and characterized in claim 5,
e.g while using a device as disclosed and characterized in
claim 11, a continuous location measurement is carried out
and, e.g. by means of an odometer or a GPS measuring de-
5   vice, it is possible to continuously store information con-
cerning the actual measurement positions together with the
measurement data, and later always be able to determine
where the individual measurements have been carried out.

10   By proceeding as disclosed and characterized in claim 6,
e.g. while using a device as disclosed and characterized in
claim 12, a complete system is obtained for the measurement
and registration of deflection which can form the basis for
the operational maintenance of the measured section. The
15   data can also be transferred in a commonly-known manner to
a databank for the surveillance and maintenance of road
sections and railway lines.

The drawing

20

The invention will now be described in more detail with
reference to the drawing, in that

        fig. 1A   shows in principle the measurement of deflec-
25   tion according to the invention on a section of
                   road,

        fig. 1B   shows in principle the measurement of deflec-
                   tion according to the invention on a train
30   rail,

        fig. 2   shows a block diagram of the measuring equip-
                   ment according to the invention,

35   fig. 3A   shows schematically the deflection at a point
                   on a road section when passed by a loaded

vehicle wheel,

fig. 3B   shows the measurement of deflection speed cor-
           responding to fig. 3A,

5

fig. 4   shows an example seen from the side of the
           mounting of a number of laser sensors on a com-
           mon, fixed measuring beam,

10   fig. 5   shows a second example, also seen from the
                 side, of the mounting of a number of laser sen-
                 sors on a common but displaceable measuring
                 beam, and

15   fig. 6   shows a third example, seen from above, of a
                 measurement setup where the common, fixed
                 measuring beam in fig. 4 is arranged trans-
                 versely to the direction of travel for the
                 measurement of the deflection arising from all
20   of the drive-wheels.

Detailed description of the embodiments shown

In fig. 1A is seen a road section 2, the deflection of
25 which is measured with a self-propelled vehicle 1 according
to the invention comprising at least one drive-wheel 4 on
an axle 6 which is loaded with a possibly displaceable or
in another way adjustable load 7 of a suitable number of
tons, e.g. 5 tons of sand. On the vehicle there is mounted
30 equipment 10 comprising an electronic measuring and regis-
tration system which is discussed later in connection with
fig. 2 of the drawing.

On the vehicle 1 there is also mounted at least one laser
35 device 8 or similar radiation-emitting device from which an
electromagnetic beam is directed towards the roadway 2. In

the example shown a laser 8 is used, the laser beam 9 of
which is directed vertically towards the roadway 2, and at
the point where the beam hits the the roadway, a reflection
point 11 arises from which the beam is reflected to all

5   sides, also including reflection to the device 8, which
also comprises a sensor for the measurement of the fre-
quency of the reflected light and herewith measurement of a
possible Doppler frequency change. There is hereby obtained
an expression for the speed of the instantaneous deflection

10   when the vehicle is driven at a suitable speed.

With a method and equipment according to the invention, it
is anticipated to be able to measure the deflection at run-
ning speeds up to 150 km/h. However, the maximum speed for

15   transport vehicles on highways in most countries is 70
km/h, so the maximum speed at which highways can be measur-
ed is thus limited to this speed.

In fig. 1B is seen a corresponding measurement on a train

20   rail 3 which is loaded by the loaded carriage wheel 5, and
where the deflection of the rail is measured, which also
includes possible ballast underlayer, sleepers etc., by
measuring the speed of the deflection at the foot of the
rail in a manner corresponding to that described above. It

25   will also be possible to measure the deflection of the
sleepers, possibly at the same time as the measuring of the
deflection of the rail, so that comparisons are possible
whereby possible faults or deficiencies can be determined
in the anchoring of the rail on the sleepers.

30

Figs. 1A and 1B are principle methods of measurement which
show how the deflection can be measured according to the
invention by measuring the deflection speed.

35   In fig. 3A is seen an example of a deflection measured at a
point on a roadway, e.g, as shown in fig. 1A. The deflec-

tion shown by the curve 13 starts at O and increases to
maximum value when the wheel passes the point, and decreas-
es again to O when the wheel has run past. Depending on the
roadway and the characteristics of the underlying struc-
5   ture, different waveforms will be obtained for the curve
13, and therefore also different degrees of maximum deflec-
tion will be obtained.

In fig. 3B is seen the speed measurements corresponding to
10   fig. 3A from the same measuring point, but measured in ac-
cordance with the method according to the present inven-
tion. The speed starts at O and increases to a maximum
speed and hereafter decreases again to O where the deflec-
tion is at a maximum (in fig. 3A), in that here the deflec-
15   tion speed is O. Hereafter, the deflection speed increases
again but in the opposite direction, as shown with opposite
polarity of the curve, to a maximum (the minimum point of
the curve 14) and decreases again towards O.

20   The measurement shown in fig. 3A is that which is attempted
to be made with the known apparatus, whereby the curve 13
is recorded, while with the method and equipment according
to the invention it is desired to measure the deflection
speed 14 shown in fig. 3B, and at the same time that this
25   is carried out continuously, i.e. points are obtained at
relatively short distances, a measurement corresponding to
the curve 14 is undertaken at each point along the section.

Fig. 4 shows an example of how a number of lasers 20, each
30   with a laser beam 21 and reflection from the roadway, can
be mounted on a common, fixed bar 19 and can continuously
measure the deflection speed of the roadway when the loaded
wheel 18 is driven in the direction of the arrow, hereby
also carrying the bar 19 in the same direction, in that
35   this is mounted on the vehicle. It will be seen that the
outermost lasers are positioned substantially outside the

deflection area, so that they can function as measurement references. The length of the bar 19 is in the order of 1-2 m. With this measuring equipment in connection with the electronic system, which is explained later in connection

5   with fig. 2, continuous measurements of the deflection of the roadway 17 can be carried out. When the vehicle is standing still, there is a static deflection which can possibly be used for control of the measuring equipment, in that the deflection speed at all lasers will be 0.

10   Fig. 5 shows another emodiment of the construction shown in fig. 4. In this case the bar 23 is suspended in a displaceable manner on a support beam 24, so that the bar and all of the lasers 20 can be moved forwards, possibly backwards, in the direction of travel to a position in which substan-

15   tially all laser devices 20 measure on that part of the roadway 17 which has no deflection. The lasers 20 can hereby be calibrated against one another.

20   In fig. 6 is seen an axle 26 in a vehicle on which twin wheels 18 are mounted at each side, all seen vertically from above. The vehicle is provided with a bar 19 in the same direction as the axle 26, i.e. transversely to the direction of travel. The bar 19 is preferably placed in

25   front of the axle 26, and at such a distance that measurements are made at the point at which maximum deflection speed is expected. It is hereby possible to measure the whole of the deflection basin 25 around the wheels 18 by means of a number, e.g. seven, of laser devices 20, which

30   as discussed above measure the speed of the deflection by means of the measured Doppler frequency change. The deflection basin 25, which spreads forwards in the direction of travel, is three-dimensional, and with the achieved measuring results distributed over a portion of the road's

35   breadth, measurement data can be obtained with which an analysis can be made of the condition of the road.

In fig. 2 is shown a block diagram which shows the rela-
tionship between the different parts of the electronic
system.

5

The whole system is mounted on a self-propelled vehicle,
e.g. a heavily-loaded vehicle with an axle load of approx.
10 tons. It is possible for the axle load to be changed by
making the load on the vehicle displaceable.

10

The equipment continuously registers the exact location
coordinate by means of the circuit 33, and from this and at
the same time the speed of the vehicle is measured at the
moment of measurement. The equipment 33 can comprise an

15   odometer or a commonly-known GPS position measuring appar-
atus.

The road curvature measurement block 34 (Trajectory) con-
tinuously measures the movement of the laser sensors during

20   the measurement by means of an INS (Initial-Navigation-
System), e.g. consisting of a fibre-optic gyroscope (FOG),
accelerometer and computers with suitable software, e.g.
from the LITEF company. The system measures all movements
in three directions. Consequently, it is possible to con-

25   tinuously calculate the exact position of the laser sensors
and the curvature of the road during the measurement. Such
measuring systems are commonly known.

The circuit 36 is used for continuous measurement of the

30   laser angle and the axle load. The laser sensors measure
the speed at right-angles to the direction in which the
laser beam spreads. If the underlayer which is measured
moves in more than one direction, it is important that the
laser beams are held as closely as possible at right-angles

35   to the direction it is desired to measure. Otherwise the
movement of the surface in other directions contributes

towards the measurement, which will hereby make the measurement inaccurate. In practice it is unavoidable that movements in other directions contribute to the measurement. There are two usable methods for making corrections
5   for the inaccurate measurements which can arise if the laser or lasers are not at right-angles to that surface from which the deflections are to be measured. It is possible either to measure the angular deviation and let the computer correct the measuring results on the basis of the
10   knowledge of how the angular deviations will influence the results of the measurement, or to use measurements of the angular deviations to control a servo-system which ensures that the angular deviation is minimal or zero. In practice it is also possible to use both correction methods simulta-
15   neously, and hereby gain the advantages of both methods. If the conditions of measurement are optimised, it is possible to separate the contributions to the measurements which arise from the speed of travel, and presumably also other undesired measurement contributions. On the basis of the
20   measuring results, a servo-control system 35 can ensure that the laser stands as vertically as possible to the road or the surface of the rail. The system consists of a measuring unit which continuously monitors the laser's angle to the vertical, and on the basis of the measurements
25   controls the servo-system to ensure that the sensors are constantly held in the vertical position. This measuring unit is suitably mounted on the chassis of the vehicle at the front and rear axle, and measures the distance to the road or the rail element as well as the distance to each
30   its wheel axle. This makes it possible to carry out a simultaneous calculation of the actual axle load.

Centrally in the unit there is provided a coordinating com-
puter 31 which, in response to commands from an operating
35   panel 32, controls the whole course of the measurement.

If the equipment is based on laser technique, use can be made, for example, of a number of laser sensors 20 of the type Dantec 55X Laser Doppler Vibrometre, or improved versions hereof. This measuring instrument measures the speed

5   at which the rail or the roadway moves downwards. It will be possible to measure both the speed of the downward deflection and the speed at which the rail or the roadway straightens out. The measurements thus provide information concerning both the elasticity and the plasticity. More-

10   over, it is anticipated that the fixture of the rails on the sleepers will give rise to periodic variations in the measuring results, and these variations can be compensated for by suitable data processing.

15   The output signals from the laser sensors are processed in a signal processing circuit 30 which, for example, is a 57N10 Burst Spectrum Analyzer from the Dantec company. The result of this processing is sent further to the coordinating computer, which at the same time receives signals from

20   the trajectory measuring unit 34 and the position measuring unit 33. The computer thus compiles data concerning the speed of the surface at the place at which the measurement is taken, and the position of the laser sensors. The data can be continuously stored in a memory 37 for later proces-

25   sing and interpretation in additional circuits 38.

C L A I M S

1. Method for non-contact measurement of the deflection of
a road or rail while loaded by a travelling vehicle with
5   weight-loaded drive-wheels, the speed of which in the di-
rection of travel is measured, c h a r a c t e r i z e d
in that the speed of the deflection is measured continuous-
ly while the vehicle is travelling by the measurement of
the vertical speed of the road or rail using sensors which
10   detect the Doppler frequency change in the reflections from
at least one unknown wave, preferably an electromagnetic
beam directed towards the roadway or the train rail, e.g.
while using a laser technique, radar technique, ultrasonic
technique or other contact-free speed measuring equipment,
15   after which the deflection can be calculated.

2. Method according to claim 1, c h a r a c t e r i z e d
in that at the same time there are carried out speed
measurements in the vertical direction at a number of posi-
20   tions at or around the loaded wheel or wheels.

3. Method according to claim 1 or 2, c h a r a c t e r -
i z e d in that the angle of the electromagnetic beam in
relation to a chosen, fixed direction, e.g. vertical, is
25   also continuously determined.

4. Method according to claim 1 or 2, c h a r a c t e r -
i z e d in that the angle of the electromagnetic beam in
relation to the trajectory of the road for the section
30   being covered is also continuously determined.

5. Method according to claim 1 or 2, c h a r a c t e r -
i z e d in that the position of the loaded wheel is also
continuously measured.

35

6. Method according to any of the claims 1-5, c h a r a c -

t e r i z e d   in that all measurement results are fed to a
data processing unit with storage facilities, either for
the continuous calculation and registration of the deflec-
tion or data which represents the characteristics of the
5   underlayer, e.g. the underlayer's rigidity, or for storage
with a view to data processing later.

7. Equipment for non-contact measurement of the deflection
of a road (2) or train rail (3) while using a vehicle (1)
10   with a load (7) which influences at least one wheel (4, 5),
the speed of which is measured in the direction of travel,
c h a r a c t e r i z e d   in that it further comprises

    a)   at least one device (8) for the transmission of a
15   wave, preferably electromagnetic radiation (9) down
       towards the roadway, the rail or the rail's under-
       layer,

    b)   at least one sensor (8) arranged to detect the
20   Doppler frequency change in the reflections (9) of
       the emitted radiation,

    c)   and an electronic circuit (10) for the continuous
       registration of the detected Doppler frequency
25   changes for the calculation of the speed of the
       deflection, and where the radiation is laser radi-
       ation, radar waves, ultrasonic signals or other radi-
       ation which gives rise to a Doppler frequency change
       at a relative movement between the device (8) and the
30   reflection point (11).

8. Equipment according to claim 7, c h a r a c t e r -
i z e d   in that it comprises a number of
devices/sensors (8) mounted on a common bar or beam (23).
35

9. Equipment according to claim 7 or 8, c h a r a c t e r -

i z e d   in that it further comprises means (36) for
measuring the angle of the electromagnetic radiation in
relation to a chosen, fixed direction, e.g. vertical.

5   10. Equipment according to claim 7 or 8, c h a r a c -
t e r i z e d   in that it further comprises means (36) for
measuring the angle of the electromagnetic radiation in
relation to the trajectory of the section of the road being
measured.

10

11. Equipment according to claim 7, c h a r a c t e r -
i z e d   in that it further comprises means (33) for the
continuous measurement of the position of the loaded wheel.

15   12. Equipment according to any of the claims 7-11,
c h a r a c t e r i z e d   in that it comprises a data pro-
cessing unit (30, 31) with storage facilities (37), either
for the continuous calculation and registration of the
measured deflection, or data which represents the charac-
20   teristics of the roadway or the train rail, e.g. its rigid-
ity, or for storage with a view to data processing later.

Fig. 1A

Fig. 1B

Block diagram


Fig. 2

Deflection

0 ⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯ Position

13

Fig. 3A

Speed

+

0 ⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯⎯ Position

−

14

Fig. 3B

18

19

20

20

21

17

Fig. 4

Fig. 5

Fig. 6

INTERNATIONAL SEARCH REPORT

	International application No.
	PCT/DK 96/00159

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: E01B 35/12, E01C 23/01, G01M 5/00
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: E01B, E01C, G01M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4781058 A (P.W. ARNBERG), 1 November 1988 (01.11.88), abstract, figures	1,7
A	SE 4781058 A (KUAB KONSULT & UTVECKLING AB), 20 April 1989 (20.04.89), page 2, line 41 - line 55	1,7

☐ Further documents are listed in the continuation of Box C.   ☒ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	
"E" erlier document but published on or after the international filing date	"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	
"O" document referring to an oral disclosure, use, exhibition or other means	"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"P" document published prior to the international filing date but later than the priority date claimed	"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
13 August 1996	13.08.96

Name and mailing address of the ISA/	Authorized officer
Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. + 46 8 666 02 86	Pia Hegele Telephone No. + 46 8 782 25 00

Form PCT/ISA/210 (second sheet) (July 1992)

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
US-A- 4781058	01/11/88	DE-A-	3585307	12/03/92
		EP-A,A,A	0175665	26/03/86
		SE-T3-	0175665	
		SE-B,C-	457807	30/01/89
		SE-A,D-	8404663	18/03/86
		US-A-	4658639	21/04/87
SE-A- 4781058	20/04/89	NONE		